



DESCRIPTION

- Cast iron body FGS 400-10
- Multimaterials and Multiplage (Compatible for PVC / PE / CAST / STEEL pipes)
- Operating temperature: / 10 ° to + 60 °
- Nitrile seal
- A.C.S certified product

PB: 40 x 3 (Metric thread)

| Réf | DN | OD (mm) | Poids |
|--------|-------|---------|----------|
| CAS001 | DN50 | 48-62 | 1,58 kg |
| CAS002 | DN65 | 57-78 | 1,65 kg |
| CAS003 | DN80 | 75-98 | 1,71 kg |
| CAS004 | DN100 | 97-118 | 1,93 kg |
| CAS005 | DN100 | 110-133 | 1,99 kg |
| CAS006 | DN125 | 126-148 | 2,05 kg |
| CAS007 | DN125 | 135-160 | 2,08 kg |
| CAS008 | DN150 | 158-177 | 2,13 kg |
| CAS009 | DN150 | 168-190 | 2,19 kg |
| CAS010 | DN175 | 182-206 | 2,25 kg |
| CAS011 | DN200 | 206-233 | 2,31 kg |
| CAS012 | DN200 | 233-254 | 2,39 kg |
| CAS013 | DN250 | 260-286 | 2,46 kg |
| CAS014 | DN250 | 285-310 | 2,55 kg |
| CAS015 | DN300 | 313-338 | 2,68 kg |
| CAS016 | DN350 | 344-372 | 8,64 kg |
| CAS017 | DN350 | 348-394 | 8,83 kg |
| CAS018 | DN400 | 394-420 | 9,25 kg |
| CAS019 | DN400 | 418-443 | 14,61 kg |
| CAS020 | DN400 | 442-475 | 14,93 kg |
| CAS021 | DN450 | 474-493 | 16,27 kg |
| CAS022 | DN500 | 500-532 | 18,96 kg |
| CAS023 | DN600 | 610-647 | 21,05 kg |
| CAS024 | DN700 | 710-738 | 24,63 kg |

GB: 55 x 3 (Metric thread)

| Réf | DN | OD (mm) | Poids |
|--------|-------|---------|----------|
| CAS101 | DN50 | 48-62 | 1,58 kg |
| CAS102 | DN65 | 57-78 | 1,65 kg |
| CAS103 | DN80 | 75-98 | 1,71 kg |
| CAS104 | DN100 | 97-118 | 1,93 kg |
| CAS105 | DN100 | 110-133 | 1,99 kg |
| CAS106 | DN125 | 126-148 | 2,05 kg |
| CAS107 | DN125 | 135-160 | 2,08 kg |
| CAS108 | DN150 | 158-177 | 2,13 kg |
| CAS109 | DN150 | 168-190 | 2,19 kg |
| CAS110 | DN175 | 182-206 | 2,25 kg |
| CAS111 | DN200 | 206-233 | 2,31 kg |
| CAS112 | DN200 | 233-254 | 2,39 kg |
| CAS113 | DN250 | 260-286 | 2,46 kg |
| CAS114 | DN250 | 285-310 | 2,55 kg |
| CAS115 | DN300 | 313-338 | 2,68 kg |
| CAS116 | DN350 | 344-372 | 8,64 kg |
| CAS117 | DN350 | 348-394 | 8,83 kg |
| CAS118 | DN400 | 394-420 | 9,25 kg |
| CAS119 | DN400 | 418-443 | 14,61 kg |
| CAS120 | DN400 | 442-475 | 14,93 kg |
| CAS121 | DN450 | 474-493 | 16,27 kg |
| CAS122 | DN500 | 500-532 | 18,96 kg |
| CAS123 | DN600 | 610-647 | 21,05 kg |
| CAS124 | DN700 | 710-738 | 24,63 kg |